

We all want to feel cosily warm in winter and pleasantly cool in summer. DCTech URSACOUSTIC MINERAL WOOL helps make this possible.

DCTech URSACOUSTIC MINERAL WOOL is a high-quality and cost-effective mineral wool with outstanding thermal and acoustic insulation properties.

DCTech URSACOUSTIC MINERAL WOOL is also extraordinarily fire resistant, making it ideal for safe thermal and sound insulation of pitch roofs, partitions, external walls and ceiling.

DCTech URSACOUSTIC MINERAL WOOL ranks among the top insulation materials in terms of their respect and protection of the environment. The energy savings generated by DCTech URSACOUSTIC MINERAL WOOL products in their end application far outweigh the energy required for their production, transport and installation; therefore DCTech URSACOUSTIC MINERAL WOOL presents a most positive energy and environmental balance.

Characteristics	Value
Designation code	MW-EN.13162-T2-WS-MU1
Lambda (λ 90/90)	0,040 W/m·K
Reaction to fire	A1—AS1530
Short term water absorption (WS)	< 1.0 kg/m ²



Suggested applications

Acoustic insulation for partitions or party walls made of gypsum boards or masonry.

Other possible applications

Thermal insulation of ceilings and walls



Thickness	Width mm	Length mm	Thermal resistance	Pack size m ² per coils	Packs per pallet
30	1.200	18.000	0.75	1260	18
45	1.200	16.200	1.10	1944	18
45	600	16.200	1.10	1944	24
45	400	16.200	1.10	1944	24
60	1.200	12.000	1.50	1440	18
70	600	10.000	1.75	1200	18
85	600	9.000	2.10	1080	18