



Innovative Finishes

Details

Innovative Finishes wall and ceiling liner panels combine the traditional benefits of fibreglass reinforced plastic (FRP) with linen and sandstone textures and tile-look and beaded finishes to provide a panel with presence and style that performs. Innovative Finishes wall and ceiling liner panels exhibit excellent resistance to mild chemicals and moisture and has a Class A rating for flame spread and smoke development when tested per ASTM E-84.



Innovative Finishes FRP panels are designed for commercial interior wall and ceiling finishes where a Class A, sanitary, easy-to-clean panel is desired.

Applications

- Restaurants and cafe's
- Reception areas
- School hallways
- Assisted living centers
- Health clubs
- Public Rest rooms

Features

- Mould and mildew resistant
- Easy to install
- Cleanable
- Durable
- Available in a variety of textures and colours

Standards

- ASTM E-84 Class A

NSW

Unit 8, 171-175 Newton Rd
Wetherill Park NSW 2164
P O Box 7186
Wetherill Park DC NSW 1851
T 02 8788 9555
F 02 9604 7468
E nsw@dctech.com.au


VIC

12 Agosta Drive
Laverton North VIC 3026
T 03 9369 7920
F 03 9369 4043
E vic@dctech.com.au



www.dctech.com.au



Technical Data

Product Name:	Innovative Finishes Fibreglass reinforced plastic panel	
Product Description:	Innovative Finishes is a commercial grade, decorative interior frp wall and ceiling liner panel system	
Finish:	Sandstone	
Product Code:	STC	
Colour:	Morning Mist Gray, Fawn Brown, Almond Breeze, Cotton White, Willow Green, Red, Blue, Daisy Gold	
Thickness:	2.3 mm	
Width x Length:	1.2 m x 2.4 m 1.2 m x 3.0 m	
Flexural Strength:	103 MPa	
Flexural Modulus:	3447 MPa	
Tensile Strength:	55 MPa	
Tensile Modulus:	4137 MPa	
Barcol Hardness:	40	
Izod Impact	0.27 J/mm	
Water Absorption:	0.16% / 24hrs @ 25°C	
Finish:	Sandstone Scored	
Product Code:	SSTC	
Colour:	Morning Mist Gray, Fawn Brown, Almond Breeze, Cotton White, Willow Green, Red, Blue, Daisy Gold	
Thickness:	2.3 mm	
Width x Length:	1.2 m x 2.4 m 1.2 m x 3.0 m	
Flexural Strength:	103 MPa	
Flexural Modulus:	3447 MPa	
Tensile Strength:	55 MPa	
Tensile Modulus:	4137 MPa	



Barcol Hardness:	40		
Izod Impact	0.27 J/mm		
Water Absorption:	0.16% / 24hrs @ 25°C		
Finish:	Linen		
Product Code:	LBCLN		
Colour:	Morning Mist Gray, Fawn Brown, Almond Breeze, Cotton White, Willow Green		
Thickness:	2.3mm		
Width x Length:	1.2 m x 2.4 m 1.2 m x 3.0 m		
Flexural Strength:	103 MPa		
Flexural Modulus:	3447 MPa		
Tensile Strength:	55 MPa		
Tensile Modulus:	4137 MPa		
Barcol Hardness:	40		
Izod Impact	0.27 J/mm		
Water Absorption:	0.16% / 24hrs @ 25°C		
Finish:	Beaded		
Product Code:	FTBB		
Colour:	Cotton White,		
Thickness:	2.3mm		
Width x Length:	1.2 m x 2.4 m 1.2 m x 3.0 m		
Flexural Strength:	97 MPa		
Flexural Modulus:	2758 MPa		
Tensile Strength:	41 MPa		
Tensile Modulus:	4137 MPa		
Barcol Hardness:	40		
Izod Impact	0.21 J/mm		
Water Absorption:	0.16% / 24hrs @ 25°C		
Finish:	Gelcoat Tile-Look with white sealed score lines		



Product Code:	SMXGC	
Colour:	White Wash, Parchment	
Thickness:	2.3mm	
Width x Length:	1.2 m x 2.4 m 1.2 m x 3.0 m	
Flexural Strength:	103 MPa	
Flexural Modulus:	2758 MPa	
Tensile Strength:	55 MPa	
Tensile Modulus:	5171 MPa	
Barcol Hardness:	45	
Izod Impact	0.21 J/mm	
Water Absorption:	0.16% / 24hrs @ 25°C	
Finish:	Gelcoat Non-Tile-Look	
Product Code:	MXGC	
Colour:	White Wash, Parchment	
Thickness:	2.3mm	
Width x Length:	1.2 m x 2.4 m 1.2 m x 3.0 m	
Flexural Strength:	103 MPa	
Flexural Modulus:	2758 MPa	
Tensile Strength:	55 MPa	
Tensile Modulus:	5171 MPa	
Barcol Hardness:	45	
Izod Impact	0.21 J/mm	
Water Absorption:	0.16% / 24hrs @ 25°C	

Glasbord & Innovative Finish Silhouette Trims

Silhouette Trims offer a narrow profile to minimise the seam.

Available in five colours to match the Innovative Finishes product





range or pattern matched for Innovative Design panel installations.

Available in White, Almond Breeze, Fawn Brown, Morning Mist Grey.

Glasbord & Innovative Finish Standard Nylon Drive Rivets

Non-staining nylon drive rivets in matching panel colours are designed for quick and easy installation using only a hammer and drill. When used with silicone sealants, drive rivets maintain an effective moisture seal as well as providing excellent mechanical fastening for panels.

Available in White, Cream, Beige, Silver and Grey.




FRP Panel Roller

Handle quickly adjusts from 43cm to 68cm. Sturdy and nickel plated. No axle projections allowing for flush work into corners.



V-Notched Trowel

8mm x 4mm x 6mm V, cold rolled blade with moulded polypropylene handle.



Advanced Polymer Adhesives

High performance, professional strength advanced polymer adhesive specifically formulated to be used for most types of paneling installations.

Recommended substrates:

Gypsum, Wallboard, Fire Rated Plywood, Pressure Treated Plywood, Fibreglass faced Gypsum, Wallboard, Mould Resistant, Gypsum, Wallboard, Ceramic, Steel, Foamboard Vinyl, PVC, FRP, Laminate and Concrete.

